

**TOUCHSTONE® CABLE GATEWAY,
DOCSIS® 3.1 GATEWAY WITH 802.11AC WI-FI & MOCA® 2.0**



FEATURES

- 2x2 OFDM and OFDMA DOCSIS® 3.1 channels
- 32x8 SCQAM DOCSIS® 3.0 channels
- Full Capture Bandwidth Tuner
- Multi Processor Technology with ARM and ATOM based Application Processor
- 4 port Gigabit Ethernet Router
- Switchable upstream filters for 42MHz or 85MHz operation.
- 4x4 Integrated Dual Band Concurrent 5GHz 802.11ac Wave2 radios and 3x3 2.4GHz 802.11n for high performance WLAN
- MoCA 2.0 (with channel bonding) for in Home Video and Data distribution over Coax
- Multiple SSID support with DFS channels and Dynamic Channel change
- Single PCB design
- Multiple operator controlled configuration options
- Designed for enhanced application support



PRODUCT OVERVIEW

The DG3450 Wireless Gateway supporting DOCSIS 3.1 allows unprecedented data rates to be delivered to MSO customers. The DG3450, along with its 4x4 802.11ac Dual Band Wireless radios, offers superior Wi-Fi performance enabling video over Wi-Fi.

The MoCA 2.0 interface with channel bonding enables the creation of a high performance home network. The switchable US duplex filter is designed to produce superior RF performance and ease of deployment on a DOCSIS 3.1 network.

Increased DRAM, Flash and Multiple embedded processor cores are designed to allow new applications to be deployed on the gateway. This feature-packed unit is intended to serve as the hub of the subscribers network, connecting all IP capable devices (Internet, Data and Video) throughout the customers premises.

Residential gateway support has always been a concern of the operator. The DG3450 distinguishes itself with capabilities to minimize these support needs. Multiple provisioning methods (SNMP, Configuration File, Remote WebGUI access, TFTP, and TR-069/181) allow custom designed setups to be applied to monitor the end user more efficiently. Multiple remote access levels (User, Cusadmin, and MSO) also allow more ease and flexibility for manual configuration and control.

The DG3450 will help lead the future to advanced home and small business services.

SPECIFICATIONS

Physical

Operating Temperature	0 to 50°C
Operating Relative Humidity	5-85% (Non condensing)
Storage Temperature	-40 to 70°C
Dimensions (H x W x D)	9.33in x 2.87in x 8in 237mm x 73mm x 205mm
Backup Capacity (not supplied)	External BBU
Weight	1.94lbs 0.88kg
Diagnostic LED's (Top)	Integrated LED for status of Power, US/DS, Online, 2.4GHz, 5GHz, Battery, MoCA
Diagnostic LED's (Rear)	MoCA, Ethernet Link/Speed

SPECIFICATIONS

Interfaces

RF Interface	1 External 'F' type connector
Date Interfaces (bridged)	4 x 10/100/1000 Base-T Ethernet (RJ-45 connector)
MoCA	MoCA 2.0
Input Voltage (nominal)	12V DC
AC-DC	External

SPECIFICATIONS

RF Downstream

Bonded Channels	Up to 32 SCQAM or 2 OFDM
Tuner Configuration	Full capture tuning range
Frequency Range (MHz)	108MHz - 1002MHz DOCSIS
Data Rate (Mbps Max.)	Up to 5Gbps
RF Input Sensitivity Level	-15dBmV to +15dBmV (DOCSIS)

RF Upstream

Bonded Channels	Up to 8 SCQAM or 2 OFDMA
Frequency Range	5MHz to 85MHz
Configurable Diplex Filter	42MHz-85MHz
Data Rate (Mbps Max.)	Up to 1Gbps
RF Output Level	+65 dBmV (64 QAM, single upstream) +57 dBmV (64 QAM, 4-8 upstreams) +65 dBmV (16 QAM, single upstream)

SPECIFICATIONS

Wireless

Frequency Range	2.4GHz and 5GHz
Transmit Power (from any antenna)	+27dBm (MCS7) +26 dBm (MCS9)
Spatial Streams	3 for 2.4GHz, 4 for 5GHz
Receive Levels	2.4GHz <-88dBm 802.11n (MCS0) , <-71dBm 802.11n (MCS7), HT20 5.0GHz <-84dBm 802.11ac (MCS0) , <-57dBm 802.11ac (MCS9), VHT80
Antennas	7 transmit, and 7 receive (total)

MoCA

Frequency Range	1150MHz –1500MHz
Network Channel Bandwidth	50MHz
Max Transmit Power	+ 9 dBm max (adjustable)
Max PhyRate	1400 Mbps
Application Data Rate	800 Mbps bidirectional combined

Note: Specifications are subject to change without notice. **Copyright Statement:** © 2016 ARRIS Enterprises, LLC. All rights reserved. No part of this publication may be reproduced in any form or by any means or used to make any derivative work (such as translation, transformation, or adaptation) without written permission from ARRIS Enterprises, LLC ("ARRIS"). ARRIS reserves the right to revise this publication and to make changes in content from time to time without obligation on the part of ARRIS to provide notification of such revision or change. ARRIS and the ARRIS logo are registered trademarks of ARRIS Enterprises, LLC. All rights reserved. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks or the names of their products. ARRIS disclaims proprietary interest in the marks and names of others.