

5800 Transmitters

DOOR/WINDOW TRANSMITTERS



The 5800 Series of door and window transmitters provide the most reliable, convenient and cost effective solutions for security protection. These devices are powerful and versatile enough to help solve even the toughest, most labor intensive installations.

With a demonstrated outdoor range of over a mile, the 5800 Series has the best performance of any transmitters available today.

FEATURES AND SPECIFICATIONS

5811 Thin Door/Window Contact Transmitter

The 5811 is ideal for applications where aesthetics are critical such as ornate doors, windows and casements.

- Single-zone transmitter
- Sleek design virtually disappears
- Transmits supervisory, tamper and low battery
- Easy-to-open case requires no special tools
- Case tamper protection
- Magnet included
- Ideal for double-hung windows
- 3V lithium battery included
- Dimensions: 2-1/8" H x 1-3/16" W x 1/4" D
- ETL Listed

5814 Ultra Small Door/Window Transmitter

The 5814 provides the perfect solution for difficult to reach places and applications where aesthetics and small size are important.

- Ideal for ornate doors/windows, casements, etc.
- Extremely compact
- Features a built-in reed switch and tamper
- Includes a supervised replaceable CR2430 battery
- Dimensions: 1-1/2" H x 1-3/16" W x 5/8" D

5815 Door/Window Transmitter

The 5815 is the ideal solution for installations where small size and aesthetics are important. It provides a reliable, convenient and cost-effective solution for door and window protection.

- New sleek design

- Two reed switches
- Transmits supervisory, tamper and low battery messages
- Includes a supervised replaceable CR123 battery
- Dimensions: 3" H x 1-1/2" W x 7/8" D
- UL Listed

5816 Door/Window Transmitter

Two zone transmitter with both built-in magnetic reed switches and wired closed circuit contact loop.

- Features a standard white plastic case. Brown cases available in packs of three (5816BR).
- Includes a supervised replaceable CR123 battery
- Four pack of spare magnets (5899)
- Dimensions: 3-1/16" H x 1-9/16" W x 1-3/16" D
- UL Listed

5800 Transmitters

DOOR/WINDOW TRANSMITTERS

FEATURES AND SPECIFICATIONS

5817XT Three Zone Universal Transmitter

Three zone transmitter with three separate contact loops. Primary loop supports normally open and normally closed applications and fast loop response time. The two auxiliary loops support conventional normally closed contact applications.

- Features a normal zone response time of 200msec; the fast zone response is 5msec
- Includes a supervised replaceable CR123 battery
- Dimensions:
3-1/2" H x 1-9/16" W x 1-3/16" D
- UL Listed

5817CBXT Wireless Commercial Transmitter

The 5817CBXT is a universal contact-monitoring transmitter that can be used with household and commercial fire and burglary-initiating devices.

- Approved for use in commercial fire and burglary

- The 5817CBXT has three unique input loops (zones)
- The first loop (primary loop) is supervised and typically used for high-priority alarm reporting such as commercial fire or burglary
- The second loop is the built-in, normally closed reed switch used in conjunction with magnet
- The third loop is another normally closed household burglary loop
- A fourth (automatically enrolled) loop contains two tamper switches to protect the 5817CBXT
- Dimensions:
3-1/2" H x 1-9/16" W x 1-3/16" D
- UL Listed

5818MNL Recessed Door/Window Transmitter

The 5818MNL is a magnetic contact sensor that provides concealed protection for doors or windows.

- Includes self-contained transmitter and reed sensor
- Virtually disappears once installed

- Easy replaceable AAA Lithium battery
- 0.5" gap (transmitter to magnet)
- Features a tapered cylinder for easy and flush fit
- Dimensions:
0.75" diameter x 3.0" length
- UL Listed

5820L Door/Window Contact Transmitter

The 5820L is nearly half the size of standard door/window transmitters. It is ideal for casement and double-hung windows.

- Sleek design is nearly half the size of competitors
- Case tamper protection (front and back)
- Ideal for double-hung windows
- Easy replaceable AAA Lithium battery
- Dimensions:
3.0" H x 0.5" W x 0.8" D
- UL Listed

ORDERING

5811	Thin Door/Window Contact Transmitter supplied with Lithium battery
5814	Ultra Small Door/Window Transmitter
5815	Door/Window Transmitter
5816	Door/Window Transmitter
5817XT	Three Zone Universal Transmitter
5817CBXT	Wireless Commercial Transmitter (UL Commercial Approved for Fire and Burglary)
5818MNL	Recessed Door Transmitter with Lithium battery supplied
5820L	Slimline Door/Window Contact Transmitter supplied with Lithium battery
5899	Four pack of spare magnets for 5816

L/5800TRAND/D
October 2014
© 2014 Honeywell International Inc.