

5822T

WIRELESS TILT SENSOR TRANSMITTER



Honeywell's 5822T Wireless Tilt Sensor Transmitter is designed to mount vertically on surfaces that tilt horizontally when opened — providing an easy way to secure garage doors or basement tilt windows. Any time the sensor detects tilt movement, a notification is transmitted to the control panel. The sensor can be programmed as a monitored or notification only zone. Includes cover tamper and battery supervision.

FEATURES

- Easy to install – use double sided tape or screws (included). Screws must be used in installations where temperatures can drop to 32°F (0°C) or below.
- Internal LED for easy programming
- Reliable 5800 Series Wireless
- Case tamper and battery supervision

SPECIFICATIONS

Battery (included)*:

1 x 3 V, Lithium

*Panasonic CR123A, Duracell DL123, Duracell DL123A or Honeywell 466

Operating Temperature:

0°F to +131°F (-17°C to +55°C)

Relative Humidity:

95% max. (non-condensing)

Dimensions:

1-9/16" W x 3-1/16" H x 1-3/16" D
(40 mm x 78 mm x 30 mm)

Compatibility:

- Honeywell 5800 Series Wireless
 - Loop 1 terminals
 - Loop 3 tilt sensor
- FCC part 15, Class B verified
- IC, ICES-003, Class B verified

ORDERING

5822T

Wireless Tilt Sensor Transmitter