

DCX3635

DUAL PLAY GATEWAY



FEATURES:

- 500 GB or 1 TB internal hard drive
- Available with the award-winning ARRIS Moxi User Interface experience
- Full Band Capture (1 GHz) 16 QAM front end
 - Standard Configuration: 6 Digital Video Tuners with DOCSIS 3.0 (8x4)
 - DOCSIS 3.0 Channel Bonding (16x4) capable with all IP configuration
- Video Decode up to 1080p60 AVC
- 2 x 1080p30 or 4 x 720p30 simultaneous transcode sessions
- Audio decode of Dolby® Digital, Dolby® Digital Plus
- MoCA® 2.0 Home Networking Interface
- Integrated Wireless Cable Modem and Router
- DOCSIS 3.0 Channel Bonding (8x4)
- 802.11ac 3x3 dual band concurrent wireless interface
- 512MB (4 Gbit) Flash, 1.5GB DRAM



PRODUCT OVERVIEW:

ARRIS has combined the advanced capabilities of a video gateway and data gateway into one device. The DCX3635 supports delivery of QAM/IP video services to the home, plus high speed internet access through the integrated cable modem and wireless router. The wireless router provides an integrated 3x3 antenna array, dual band concurrent radios, and BeamForming to provide reliable Wi-Fi coverage throughout your home. The DCX3635 also provides a whole home solution for delivering video content to connected devices via MoCA 2.0, Ethernet, and Wi-Fi.

DCX3635
Dual Play Gateway

Advanced Features

The DCX3635 Dual Play Gateway includes state-of-the-art features. The front end of the DCX3635 is flexible, which allows the operator to deliver a mixture of services via QAM and IP to its tuners. So it can be configured to tune up to 6 QAM services simultaneously, with 8 DOCSIS downstream channels. Alternatively, the DCX3635 can be configured to use all 16 channelizers in the 1GHz Full Band Capture front end for delivering IP video and providing internet access.

Another key feature for the DCX3635 Dual Play Gateway is the built in transcoding capabilities. Transcoding allows it to take QAM MPEG-2 services, transcode it to MPEG-4 for delivery to mobile devices (tablets, smart phones) over the home Wi-Fi network. The DCX3635 can decode and display video content up to 1080p60 for the main display, plus additional video decodes to support either quad transcoding sessions up to 720p30 or dual up to 1080p30.

Improved Watch and Record Capabilities

The ARRIS Whole Home Solution supports multi-room viewing of all broadcast, recorded, home network and internet content for a truly converged entertainment experience. This six-tuner whole home system enables subscribers to record as many as 6 HD channels simultaneously. Remote scheduling via internet browser devices enables operators to meet growing customer expectations to remotely schedule and dynamically manage recordings and scheduling conflicts when away from home. Users can also access Internet video and other content such as news, sports, market, or weather information.

STANDARD INTERFACES

Front Panel

- Power, Home LAN, Record, Wi-Fi and High Speed Data LEDs
- RF4CE wireless interface
- IR remote control sensors

Rear Panel

- F-connector for Cable input
- HDMI™ 1.4 output
- Baseband composite video output
- L/R audio output with volume control
- Optical S/PDIF digital audio output
- USB 2.0 Host Type A port
- (2) 10/100/1000 Ethernet interface
- eSATA interface
- Mini-iphone 3.5mm serial port and External IR input
- Cable Modem Reset and WPS Buttons



GENERAL SPECIFICATIONS

RF Input Frequency:	54 MHz to 1002 MHz (audio/video)
Tuning:	1GHz Full-Band Front End 16x 64-1024 QAM Demodulators DOCSIS 3.0 channel bonding
Memory:	512MB Flash, 1.5GB DRAM
Video:	Triple video decode (one local, two transcode) up to 1080p60, MPEG-2, MPEG-4 AVC, SVC, MVC
Composite Video Output Formats:	NTSC, PAL-M, and PAL-Nc
HDMI Video Output Formats:	480i/p, 576i/p, 720p, 1080i, and 1080p24/30/60
Audio:	Dolby Digital, Dolby Digital Plus, Dolby Dialogue Clarity
Transcode:	Quad transcode up to 720p30 each, or dual transcode up to 1080p30
Graphics:	1.2 Gp/s OpenGL 2.0, scalable video-in-graphics
Wi-Fi	802.11n, 2.4GHz, 3x3 MIMO, 20/40 MHz channels 802.11ac, 5GHz, 3x3 MIMO, 20/40/80 MHz channels
Hard Disk Drive:	500GB standard, 1 TB option
Out-of-Band Modulation:	Frequency agile receiver 70 MHz to 130 MHz
Power Supply:	100 VAC to 240 VAC, 50/60 Hz input; 12 VDC output
Power Dissipation:	46 W AC (depending on features)
Dimensions:	324mm Wide x 228mm Deep x 63mm High
Weight:	2.02 kg
Operating Temperature:	15 °C to 42 °C (50 °F to 108 °F)
Operating Humidity:	5% to 90% (non-condensing)



Specifications are subject to change without notice.

©ARRIS Enterprises, Inc. 2015 All rights reserved. No part of this publication may be reproduced in any form or by any means or used to make any derivative work (such as translation, transformation, or adaptation) without written permission from ARRIS Enterprises, Inc. ("ARRIS"). ARRIS reserves the right to revise this publication and to make changes in content from time to time without obligation on the part of ARRIS to provide notification of such revision or change. ARRIS and the ARRIS logo are all registered trademarks of ARRIS Enterprises, Inc. MoCA is a registered trademark of Multimedia over Coax Alliance. HDMI is a trademark of HDMI Licensing LLC. Dolby and the double-D symbol are registered trademarks of Dolby Laboratories. This product incorporates copy protection technology that is protected by U.S. patents and other intellectual property rights. Use of this copy protection technology must be authorized by Rovi Corporation, and is intended for home and other limited viewing uses only unless otherwise authorized by Rovi Corporation. Reverse engineering or disassembly is prohibited. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and the names of their products. ARRIS disclaims proprietary interest in the marks and names of others. All other product or service names are the property of their respective owners. The capabilities, system requirements and/or compatibility with third-party products described herein are subject to change without notice.