



## iPCAM-PT

WIRED/WIRELESS INDOOR IP CAMERA WITH PAN/TILT ABILITY

### FEATURES AND SPECIFICATIONS

---

#### Video

- **Image Sensor** – CMOS 1/4" VGA resolution
- **LENS** – F2.0 Fixed Focus, Effective range: 50cm to infinity
- **Compression** – MPEG-4/M-JPEG Dual Stream
- **Resolution** – Support 640 x 480
- **Frame Rate** – Up to 30 frames per second in VGA (640 x 480)
- **Image Control** – AWB, AGC, Sharpness, Brightness

#### Pan/Tilt

- **Pan Range** – 300° (Left 150° ~ Right 150°) + 53° View Angle
- **Tilt Range** – 120° (Up 90° ~ Down 30°) + 53° View Angle

#### Wireless (RC8061)

- **Standard** – IEEE 802.11g
- **Encryptions** – WEP 64 Bits/128 Bits, WPA/WPA2 Personal, WPS

#### Hardware

- **LED Indicators** – Power, Active, Network
- **Connector Ethernet** – RJ-45, DC Power, Reset, External Microphone
- **Motion Sensor** – 15 ft., 100° area coverage
- **Bright Light LED** – Four white light LEDs light up to 15 ft.
- **Privacy Button** – Privacy button for video enable/disable
- **Power Adapter** – 5V/2A, 100 VAC
- **Certification** – CE/FCC Listed
- **Dimensions** – 5.7" H x 3.8" W x 3.1" D
- **Weight** – 1.5 lbs.
- **Operating Temperature** – 23°F – 122°F (-5°C – 50°C)

## Honeywell Total Connect™

VIDEO SOLUTIONS



Honeywell Total Connect Video Solutions are part of Honeywell Total Connect Remote Services, which let consumers control their security and automation systems, view live video and receive important email and video notifications on mobile devices anytime, anywhere. It provides dealers with an excellent way to earn RMR.

Wired/Wireless IP Cameras are easy to install and feature a compact, portable design — allowing consumers to move them whenever they choose. Low-light, pan/tilt and outdoor versions are also available. Honeywell's WAP-PLUS (Wireless Access Point) provides secure, wireless networking ability (Wi-Fi®) in iPCAM installations. It connects easily to a port on a router and is configured with iPCAMs using Wi-Fi Protected Setup (WPS).

Honeywell's WREX (Wi-Fi Repeater Extender) is designed to enhance connectivity within a wireless Wi-Fi network. The WREX connects between a WPS (Wi-Fi Protected Setup) enabled access point or router (e.g., WAP-PLUS) and wireless client device(s) (e.g., Honeywell Total Connect Remote Services IP cameras) to increase the coverage of the existing wireless network.

Wi-Fi signal strength bars and a diagnostic screen appear in web-based Honeywell Total Connect in order to help installers diagnose range issues, most of which can be resolved by adding the WREX Wi-Fi Repeater Extender. Since the cameras are portable, it will help users diagnose why cameras have stopped working if moved to a new location.

## Video Solutions



## FEATURES AND SPECIFICATIONS

- Works with PCs, smartphones, tablets and other compatible wireless devices.
- Video signal strength indicator
- Video diagnostic screen
- Advanced graphic user interface – The Honeywell Total Connect video viewer is an attractive, easy to use interface with customizable multiple images, sizing capability and streaming views. Optional pan/tilt controls for compatible cameras.
- Adobe® Flash player-based application
- QuickTime® video player
- Secure communications firewall friendly video streaming – No router changes required, no port forwarding necessary
- Web-based camera configuration – Video application parameters configured via Honeywell Total Connect
- Up to six cameras supported per account – Selectable per user multi-camera view
- Event driven video notification with adjustable video motion detection technology
- Video storage of up to 100MB of video clips

Adobe and Flash are registered trademarks of Adobe Systems Incorporated in the United States and/or other countries. QuickTime is a registered trademark of Apple Inc.