

The **Terrace TC600E** MDU gateway is a multi-channel QAM to analog RF converter with support for MPEG-2 and H.264 content. The Terrace TC600E can demodulate up to 36 QAM channels, decrypt up to 36 programs using 6 Multi-Stream CableCARDS™, decode up to 36 MPEG-2 HD/SD or 24 H.264 HD programs, and output up to 36 NTSC analog channels. The Terrace TC600E is a flexible, compact and cost effective way to bring a digital lineup back into the analog realm for a commercial or MDU bulk account.



Features

- Highly integrated - Combines QAM demodulation, decryption, NTSC modulation and RF upconversion
- Supports MPEG-2 and H.264 video decoding
- Demodulate up to 36 QAM channels
- Convert up to 36 MPEG-2 HD/SD or 24 H.264 HD programs to analog channels
- Supports up to 6 Multi-Stream CableCARDS to decrypt up to 36 streams
- SCTE-18 Force Tune EAS Support
- SCTE-20,21 Closed Captioning / VBI support
- Integrated DOCSIS 3.0 cable modem
- Supports IPv4 and IPv6
- Scalable – combine up to 3 co-located units to generate 90 contiguous channels
- Compatible with HITS QT+
- Compact 1RU design saves space and power

RF Input Port

Connector	F-Connector, female
Input Impedance	75 Ω
Return Loss	15 dB (5 - 42 MHz and 54 - 1002 MHz)
Modulation	64, 256 QAM (Annex B)
Frequency	54 - 1002 MHz (Band Edges)
Channels	36
Input Level	-12 to 15 dBmV

Conditional Access System

Type	MediaCipher®, PowerKEY™
Format	CableCARD™

Video

Format	MPEG-2, MP@ML MPEG-2, HP@HL H.264, High Profile, Level 4.0
Bitrate	Up to 17 Mbps

Audio

Format	Dolby Digital® (AC-3)
Bitrate	Up to 512 kbps
Sample Rates	32 kHz, 44.1 kHz, 48 kHz
Downmix	Multichannel downmix to stereo or mono

RF Output

Connector	F-Connector, female
Impedance	75 Ω
Return Loss	13 dB (54 to 600 MHz)
Video	NTSC
Audio	Licensed BTSC/SAP
Frequency	54 to 600 MHz (EIA channels 2 to 86, 95 to 99)*
Channels	36 channels within a 48 channel (294 MHz) frequency block
Output Level	26 dBmV ± 2.5 dB
Carrier-to-Noise Ratio	> 49 dB/4 MHz
Composite Triple Beat	< -52 dBc
Composite Second Order	< -55 dBc
Cross Modulation	< -52 dBc
Inband Spurious (-0.75 to +4.2 MHz relative to video carrier)	< -51 dBc

* FCC and per channel offsets supported

Ethernet Management Port

Connector	RJ45
Speed	10/100BASE-T Ethernet

Craft Interface Port

Connector	USB Type B, receptacle
-----------	------------------------

Ethernet Media Port (Future use)

Connector	RJ45
-----------	------

Emergency Alert System (EAS)

EAS Compliance	ANSI/SCTE-18 2007 Force-Tune
----------------	------------------------------

Closed Captioning / VBI

Input Format	ANSI/SCTE-20 2004 ANSI/SCTE-21 2001
Output Format	CEA-608-E R-2014

Control & Management

Supported Protocols	HTTPS, SSH, DHCP, TFTP, IPv4/IPv6, TACACS+ ** SNMP **
---------------------	---

**** Feature/specification planned for future availability.***Inquire with Vecima Sales Representative for more information***Chassis / Power / Environmental**

Dimensions (H x W x D)	4.5 cm x 48.3 cm x 55.9 cm (1.7 in. x 19 in. x 22 in.)
Weight	5.8 kg (12.75 lbs.)
Input Voltage	100 to 240 VAC, 47 to 63 Hz
Power Consumption	< 175 W
Temperature (Operational)	0 to 50°C (32 to 122°F)
Humidity (Operational)	5 to 95% non-condensing
Temperature (Storage)	-40°C to 70°C (-40°F to 158°F)
Humidity (Storage)	5 to 95% non-condensing
ROHS & WEEE Compliant	Yes

Regulatory Standards Compliance

Safety	CAN/CSA-C22.2 No. 60950-1-07, 2nd Ed. ANSI/UL Std No. 60950-1-2011, 2nd Ed.
EMC Emissions	FCC Part 15 Class B (ANSI C63.4: 2009) ICES-003 Issue 5: 2012

TC600E supports flexible channel plans as shown⁽¹⁾

TC600E Channel Plan	Contiguous Encrypted Lineup (with FM)	Contiguous Encrypted Lineup (no FM)	Number of CableCARDS Required*
Single Unit	36 Channels		6 Total
TC600E (EIA = 2)	2-32, 95-99	2-37	6
TC600E (EIA = 33)	33-68 ... 42-77	33-68 ... 42-77	6
TC600E (EIA = 39)	42-77 ... 51-86	42-77 ... 51-86	6
Dual Stack	72 Channels		12 Total
TC600E (EIA = 2)	2-32, 95-99	2-37	6
TC600E (EIA = 33)	33-68	38-73	6
Triple Stack	90 Channels	85 Channels	15 Total
TC600E (EIA = 2)	2-32, 95-99	2-37	6
TC600E (EIA = 33)	33-68	38-73	6
TC600E (EIA = 39)	69-86	74-86	3

* CableCARDS required assumes fully encrypted channel lineup with 6 channels per CableCARD. Unencrypted channels are not counted against the CableCARD decryption limit.

⁽¹⁾ The TC600E supports flexible channel plans via web gui and console port. Select the lowest EIA number (EIA = 2, 33 or 39) of the desired Channel Plan and the TC600E will derive the appropriate channels for that plan.The TC600E can output up to 36 channels within a 294 MHz (48 channel) frequency block allowing the user to enable 36 non-contiguous channels
For example: 2, 4-7, 9-15, 17-30, 33-41, 45

MediaCipher is a registered trademark of ARRIS | PowerKey is a registered trademark of Cisco Systems | CableCARD is a trademark of Cable Television Laboratories, Inc. | DOCSIS is a registered trademark of Cable Television Laboratories, Inc. | Dolby Digital is a registered trademark of Dolby Laboratories