



PRODUCT OVERVIEW:

The Touchstone® DOCSIS® 3.0 32x8 Cable Modem CM3200 delivers a full Gigabit per second of raw speed, ushering in a new era of Internet access! The CM3200 is well-suited to the home user – offering the speeds to stream multimedia content to multiple devices and the responsiveness to keep you “in the game” for online gaming. However, the CM3200 is also a serious commercial solution, ready to meet the challenging demands of small business with its Business Services over DOCSIS (BSoD) support. So, whether you’re at work or at play, the CM3200 is there to make sure your experience is ahead of the rest.

Touchstone® DOCSIS® 3.0 Upgradeable 32x8 Cable Modem CM3200



- DOCSIS® 3.0 Certified and backward compatible
- External AC/DC Adapter for reduced product size
- Flexible DS x US channel bonding support (up to 32x8)
- DS Spectrum Analysis, Speed Test, and LEDs for fast troubleshooting
- Business Services over DOCSIS (BSoD) support
- Available in 42MHz and 85MHz upstream (future) options

GENERAL SPECIFICATIONS

Physical	
Operating Temperature °F (°C)	32 to 104 (0 to 40)
Operating Relative Humidity (Min-Max)	5-95% (non-condensing)
Storage Temperature °F (°C)	-40 to 158 (-40 to 70)
Dimensions (H x W x D) in. (cm) <i>Excludes F-connector</i>	5.9 x 5.3 x 1.8 (15.0 x 13.5 x 4.6)
Weight lbs (kg)	0.77 (0.35)
Diagnostic LEDs	Power, US/DS, Online, LAN
Interfaces	
RF Interface	External 75Ω 'F' type connector
Data Interface	10/100/1000 Base-T Ethernet RJ-45
Power Interface (nominal)	Adapter input = 115-240 VAC, 50/60 Hz Adapter output (to CM3200) = 12V/2A
RF Downstream	
Frequency Range (MHz)	CM3200A/NA: 88-1002 (edge-to-edge) CM3200A/NA-85: 108-1002 (edge-to-edge)
Bonded Channels	Up to 32
Tuner Configuration	Full capture tuning range
Modulation (QAM)	64 or 256
Data Rate (Mbps, Theoretical)	Up to 1000 (limited by GigE interface)
RF Input Sensitivity Level (dBmV)	-15 to +15
Carrier Bandwidth (MHz)	6
MoCA® Immunity Filter	Embedded

GENERAL SPECIFICATIONS (continued)

RF Upstream	
Frequency Range (MHz)	CM3200A/NA: 5-42 CM3200A/NA-85: 5-85
Bonded Channels	Up to 8
Modulation	QPSK, 8QAM, 16QAM, 32QAM, 64QAM, 128QAM (S-CDMA only)
Modulation Bandwidth (kHz)	TDMA: 200, 400, 800, 1600, 3200, 6400 S-CDMA: 1600, 3200, 6400
Data Rate (Mbps, Theoretical)	Up to 240 <i>Max raw DOCSIS rate; actual throughput is less due to overhead, configuration, and RF conditions</i>
RF Output Level (dBmV-1 channel)	TDMA: +17-61 (QPSK); +17-58 (8QAM, 16QAM); +17-57 (32QAM, 64QAM) S-CDMA: +17 to +56 (all modulations) Note1: A-TDMA max output reduced 3dB when transmitting 2 channels (6dB when transmitting 3+ channels). Extended US power compensates at higher bonding levels to ensure max output does not drop below +54dBmV. Note2: S-CDMA max output reduced 3dB when transmitting 2 or more channels.
Automatic Level Adjust	Yes
Frequency Stability (kHz)	±5
Output Impedance (Ω)	75
Standards	
DOCSIS® 3.0 Certified	UL® 60950 / CB
FCC Part 15 Class B	RoHS / WEEE
IEEE 802.3, IEEE 802.3ab	

ORDERING INFORMATION

Part #	Description
1000030	CM3200A/NA, DOCSIS 3.0 CM, Ships in 32x8 Configuration, 115-240VAC 50/60Hz (external adapter), NA Power Cord, 1x GigE, No USB, RoHS
TBD	CM3200A/NA-85, DOCSIS 3.0 CM, Ships in 32x8 Configuration, 5-85MHz US, 115-240VAC 50/60Hz (external adapter), NA Power Cord, 1x GigE, No USB, RoHS

©ARRIS Enterprises, Inc. 2015 All rights reserved. No part of this publication may be reproduced in any form or by any means or used to make any derivative work (such as translation, transformation, or adaptation) without written permission from ARRIS Enterprises, Inc. ("ARRIS"). ARRIS reserves the right to revise this publication and to make changes in content from time to time without obligation on the part of ARRIS to provide notification of such revision or change. ARRIS and the ARRIS logo are all trademarks of ARRIS Enterprises, Inc. Other trademarks and trade names may be used in this document to refer to either the entities claiming the marks and the names of their products. ARRIS disclaims proprietary interest in the marks and names of others. **Note:** The capabilities, system requirements and/or compatibility with third-party products described herein are subject to change without notice.