

# AlphaCell® XTV International

## EXTREME TEMPERATURE CABLE BROADBAND BATTERIES



- **Extreme temperature** Absorbed Glass Mat (AGM) technology
- **Significant cold temperature** performance improvement over gel
- **Longer runtimes** help increase network reliability
- **Multiple models** provide options for all network architectures
- **Power density** gains allow more runtime from smaller sized battery
- **Extended service life** for non-temperature controlled outdoor enclosures
- **Full 4-year** replacement warranty



**The AlphaCell XTV Battery line is specifically designed for extreme outdoor temperature applications. Its virgin lead-alloy grids minimize corrosion and maximize life expectancy.**

Patented Computerized Charge/Discharge System (CCDS) provides 100% out-of-box runtime capacity. Strategic global manufacturing and distribution locations available with non-spillable transportation ratings. Optimized for remote advanced status monitoring.

General	100XTV	150XTV	195XTV	240XTV
<b>Operating Temperature Range</b> (w/ Temperature Compensation):	-40 to 60°C / -40 to 140°F (charger temperature compensation @ ±3.3mVpc per °C)			
<b>Storage Temperature:</b>	-10 to 40°C / 14 to 104°F	-10 to 40°C / 14 to 104°F	-10 to 40°C / 14 to 104°F	-10 to 40°C / 14 to 104°F
<b>Self Discharge:</b>	Battery can be stored up to 12 months at 25°C / 77°F. Higher temperatures during storage will require more frequent recharge.			
<b>Voltage Per Unit:</b>	12V	12V	12V	12V
<b>Float Charge Voltage:</b>	13.5 to 13.8VDC average per 12V unit at 25°C / 77°F			
<b>Refresh/Boost Charging Voltage:</b>	14.4 to 15.0VDC average 12V unit at 25°C / 77°F			
<b>Maximum AC Ripple (Charger):</b>	0.5% RMS or 1.5% of float recommended for best results. Maximum voltage allowed = 4% P/P			
<b>Terminal Type:</b>	Threaded alloy insert terminal to accept M6 x 12mm bolt	Threaded alloy insert terminal to accept M6 x 20mm bolt		
<b>Terminal Hardware Torque:</b>	13.6NM / 120in-lbs	13.6NM / 120in-lbs	13.6NM / 120in-lbs	13.6NM / 120in-lbs
<b>Case Sizes:</b>	22NF	24	27	31
<b>Dimensions H x L x W (mm/in):</b>	207 x 228 x 138 / 8.17 x 9.01 x 5.46	214 x 275 x 168 / 8.44 x 10.85 x 6.65	214 x 322 x 169 / 8.43 x 12.71 x 6.67	217 x 343 x 170 / 8.57 x 13.50 x 6.71
<b>Weight Approximate (kg/lbs):</b>	17.7 / 39	25.4 / 56	30.5 / 67	32 / 75

Battery	100XTV	150XTV	195XTV	240XTV
<b>Runtime Rating 25A</b> (@ 25°C / 77°F to 1.75Vpc):	100 minutes	150 minutes	195 minutes	240 minutes
<b>Amp Hour Capacity 20Hr Rate</b> (@ 25°C / 77°F to 1.75Vpc):	56Ah	80Ah	100Ah	112Ah
<b>Maximum Discharge Current:</b>	300A	800A	800A	850A
<b>Short Circuit Current:</b>	1450A	1900A	2250A	2650A
<b>Impedance 60Hz</b> (approximate):	0.005Ω	0.0045Ω	0.0039Ω	0.0034Ω
<b>Conductance Range Fully Charged New Battery</b> (@ 25°C / 77°F):	700 - 800	900 - 1100	1050 - 1250	1250 - 1550

Terminal hardware included with every battery

Constant Current Nominal Ratings in Amps (@ 25°C / 77°F to 1.75V per Cell)											
Discharge Time (Hours)	1	2	3	4	5	6	8	10	12	20	
<b>100XTV:</b>	39.4	22.1	15.8	12.4	10.3	8.7	6.7	5.4	4.6	2.8	
<b>150XTV:</b>	53.0	30.6	21.6	16.8	13.9	11.9	9.3	7.7	6.5	4.0	
<b>195XTV:</b>	65.5	37.6	26.9	21.0	17.3	14.7	11.3	9.4	7.9	5.0	
<b>240XTV:</b>	81.7	45.5	32.1	25.0	19.8	16.6	13.0	10.5	9.0	5.6	

Estimated Runtime Minutes Using XM3-918HP (Deduct 4-6% for Legacy XM Power Supplies)																
90VAC @	4A				6A				8A				10A			
Models:	100XTV	150XTV	195XTV	240XTV	100XTV	150XTV	195XTV	240XTV	100XTV	150XTV	195XTV	240XTV	100XTV	150XTV	195XTV	240XTV
<b>3 Batteries:</b>	280	401	506	581	183	262	335	389	133	190	245	289	101	146	190	228
<b>6 Batteries:</b>	597	869	1083	1240	402	579	726	830	298	427	538	617	232	332	421	485
<b>9 Batteries:</b>	914	1349	1673	1927	621	905	1128	1292	465	672	841	961	366	527	662	757
90VAC @	12A				14A				16A				18A			
Models:	100XTV	150XTV	195XTV	240XTV	100XTV	150XTV	195XTV	240XTV	100XTV	150XTV	195XTV	240XTV	100XTV	150XTV	195XTV	240XTV
<b>3 Batteries:</b>	81	117	153	188	66	96	127	158	55	81	108	136	47	69	92	118
<b>6 Batteries:</b>	188	269	344	399	157	224	288	336	133	191	246	290	113	163	211	251
<b>9 Batteries:</b>	300	430	542	621	252	360	456	524	215	307	391	451	185	264	337	391

Estimated Runtime Minutes Using XM3-624HP (Deduct 4-6% for Legacy XM, VMX, and GMX Power Supplies)																
60VAC @	4A				6A				8A				10A			
Models:	100XTV	150XTV	195XTV	240XTV	100XTV	150XTV	195XTV	240XTV	100XTV	150XTV	195XTV	240XTV	100XTV	150XTV	195XTV	240XTV
<b>3 Batteries:</b>	416	599	751	858	276	396	500	574	203	290	369	427	157	224	288	336
<b>6 Batteries:</b>	869	1280	1588	1828	590	858	1070	1225	441	637	797	912	347	499	627	717
<b>9 Batteries:</b>	1321	1941	2441	2832	904	1333	1653	1904	681	995	1237	1419	539	783	977	1118
60VAC @	12A				14A				16A				18A			
Models:	100XTV	150XTV	195XTV	240XTV	100XTV	150XTV	195XTV	240XTV	100XTV	150XTV	195XTV	240XTV	100XTV	150XTV	195XTV	240XTV
<b>3 Batteries:</b>	126	181	234	276	104	150	195	233	87	127	166	201	74	108	142	175
<b>6 Batteries:</b>	284	407	513	589	238	340	431	497	203	291	370	428	174	249	319	371
<b>9 Batteries:</b>	444	641	803	918	375	539	677	774	322	432	582	667	278	398	503	577

Based on .92 cable plant factor @ 25°C / 77°F