

MSE-200

DUAL CHANNEL H.264 ENCODER, HDMI OR COMPONENT VIDEO & AUDIO





The MediaSteam, MSE-200 is a powerful dual channel video encoder allowing two independent FullHD video streams to be broadcast or recorded at the same time. The MSE-200 has two HDMI or two component video/audio interfaces (mix & match) supporting up to 1080p@60, HD video inputs. Encode two independent video streams simulataneously to the same network or each channel can be stream separately on different networks. MSE-200 has a high quality, dual H.264 High-Profile codec, which enables live streaming, IPTV and multicasting applications. Additionally, this feature rich, cost effective encoder can support streaming not only for LAN applications, but also supports internet streaming protocols and streaming to the most popular CDN's such as Facebook Live, YouTube, UStream, Amazon Web Services, Akamai, Wowza and Twitch; these features make it simple to broadcast content to a virtually unlimited audience.

Features

- Dual channel, High Profile, H.264 encoding
- HDMI or component video and audio
- Supports RTP, UDP, TCP, RTMP & RTSP streaming
- Compatible streaming to many CDN's
- Resolutions support up to 1080P@60
- User friendly, easy to use WebUI
- Three modes: dual channel, splitter or recording
- Unicast or multicast streaming
- Space saving, compact design



Advanced technologies that connect your AV Network



MSE-200

OPTICONN TECHNOLOGIES THAT CONNECT

Dual channel H.264 Encoder, HDMI or Component Video & Audio

Models

Model	Description
MSE-200	Dual channel encoder, H.264, HDMI or component video, RCA audio L/R, Unicast or Multicast UDP or RTP, TCP, RTMP, RTSP, CDN compatibilty for Wowza, Facebook Live, You-Tube, Amazon Web Services, Twitch, Akamai, and UStream, 12VDC@1.5A power adapter included

POWER LED LAN LED'S DATA LED'S OPTICONN LEFT AUDIO IN 2 RIGHT AUDIO IN 2 COMPONENT → LAN A VIDEO IN 2 LAN B ON/OFF • 12VDC COMPONENT RIGHT AUDIO IN 1 VIDEO IN 1 LEFT AUDIO IN 1 HDMI IN 2 HDMI IN 1

Specifications

Video Specifications		
Inputs	2ch HDMI 2ch Component Video	
Input Resolutions	Auto-detect NTSC or PAL, 720p 50/60, 1080i 50/60, 1080p 25/30/50/60	
Encoding Format	H.264 High/Main/Baseline Resolution 320x240 up to 1920x1080	
Bit Rate Adjustment	200 Kbps to 15 Mbps	
Audio Specifications		
Audio Encoding Format	AAC-LC mono/stereo	
Bit Rate	64 to 512 Kbps	
Connections	RCA L/R	
Streaming Specifications		
Protocols	UDP (Unicast & Multicast), RTP (Unicast & Multicast) TS-TCP, RTSP, RTMP	
CDN Compatibilty	Wowza, Facebook Live, UStream, Amazon Web Services, Akamai, Twitch, YouTube	
Modes	Dual channel, Splitter & Record	
Network Specifications		
Interface	RJ45 10/100 Mbps	
Mechanical Specification		
Enclosure type	Stand-alone	
Dimensions (L x W x H)	9" x 4.88" x 1.65"	
Weight	1.98 lbs	
Power Specifications		
Power Supply	12VDC@2A	
Environmental Specifications		
Operating Temperature	0 to 50 C	
Relative Humidity	0 to 80%, non-condensing	
Storage Temperature	-30 to 65 C	

www.amt.com

