

# miniCMTS200a

## MINI CABLE MODEM TERMINATION SYSTEM



miniCMTS200a  
(front view)

An alternative to larger, more expensive cable modem termination systems (CMTS) & second-hand units with low bandwidth, ATX's miniCMTS is designed to provide smaller cable operators with the capabilities they need at an exceptional value. The low-cost unit supports up to 400 cable modems depending on the usage model & cable modem type (maximum of 250 DOCSIS® 3.0 + 150 DOCSIS 2.0 or 400 DOCSIS 2.0). We recommend a maximum of 400 modems for hospitality applications & a maximum of approximately 200 modems for residential applications or anywhere that a higher usage model applies.

The miniCMTS offers 16 downstream bonded channels for up to 800 Mbps downstream /120 Mbps upstream data delivery. In a residential setting with 200 modems, this data rate provides for a 4 Mbps uncontended Internet connection per subscriber.

### Features

- Optimized for smaller cable operators
- Supports up to 400 DOCSIS cable modems
- Offers 16 downstream bonded channels
- Provides high-speed data delivery: 800 Mbps downstream & 120 Mbps upstream
- Features an intuitive web interface for simple configuration, management & debugging



miniCMTS200a  
(rear view)

### Specifications

DOWNSTREAM CHANNEL	
QAM MODULATION MODE	Annex A, B
QAM MODULATION	64 QAM, 256 QAM
DATA RATE	36 Mbps @ 64 QAM, 50 Mbps @ 256 QAM
DOWNSTREAM CHANNEL QUANTITY	16-channel
DOWNSTREAM MAX. SPEED	800 Mbps
FREQUENCY RANGE	87-1000 MHz
CHANNEL BANDWIDTH	8 MHz/6 MHz
OUTPUT POWER	49 dBmV (8-channel) 45 dBmV (16-channel)
POWER ADJUSTED RANGE	Adjusted 25 dB, Step Size 0.5 dB
PRE-EQUALIZED MER	42 dB
UPSTREAM CHANNEL	
UPSTREAM MODULATION	QFSK, 16 QAM, 64 QAM
DATA RATE	30 Mbps @ 64 QAM (6.4 MHz)

UPSTREAM CHANNEL (cont'd)	
UPSTREAM CHANNEL QUANTITY	4-channel
UPSTREAM MAX. RATE	120 Mbps
INPUT FREQUENCY RANGE	5-65 MHz
INPUT LEVEL RANGE	Bandwidth 6.4 MHz, -7 dBmV to 23 dBmV Bandwidth 3.2 MHz, -10 dBmV to 20 dBmV Bandwidth 1.6 MHz, -13 dBmV to 17 dBmV
RF OUTPUT	
RF IN CONNECTOR (Upstream)	1x F Connector, 75 Ω
RF OUT CONNECTOR (Downstream)	1x F Connector, 75 Ω
PORT INSERT LOSS	< 4 dB
PORT REFLECT LOSS	< -12 dB
DATA PORT	
NET PORT RATE	10/100/1000 Mbps
NET PORT TYPE	Managed Connector, 1x RJ45 Data Connector, 1x SFP & 1x RJ45

## Specifications (cont'd)

### miniCMTS200a

COMMUNICATION INTERFACE (cont'd)	
<b>COMMAND LINE INTERFACE (CLI)</b>	RS232 Serial Port Telnet or SSH
<b>SNMPv2</b>	DOCSIS MIBs
OTHER FUNCTIONS	
<b>MAX. CABLE MODEM AMOUNT</b>	400 DOCSIS 2.0 400 (Max. 250 DOCSIS 3.0 + 150 DOCSIS 2.0)
<b>DYNAMIC LOAD BALANCED</b>	Supported
<b>DHCP RELAY</b>	Supported
GENERAL	
<b>OPERATING TEMPERATURE</b>	-10°C to +50°C (+14°F to +122°F)
<b>HUMIDITY</b>	10-90%
<b>POWER</b>	< 35 Watts (without Optical Receiver) < 45 Watts (with Optical Receiver)
<b>POWER SUPPLY</b>	220V/110V
<b>DIMENSIONS</b>	1.75"H x 19.0"W x 16.0"D (4.45H x 48.26W x 40.6D cm)

## Ordering Information

Part Number	Description
<b>miniCMTS200a</b>	Mini Cable Modem Termination System
<b>MCMTS-SF</b>	One year annual support and service fee for miniCMTS200a

Products or features contained herein may be covered by one or more U.S. or foreign patents. DOCSIS® and other non-ATX product and company names mentioned in this data sheet are the property of their respective companies.

© 2018 ATX Networks  
Printed in Canada  
Information in this document is subject to change without notice.  
Rev. 05/18 (ANW1271)

